

720 Nitrile



Polyester/nylon knit Nitrile coating

DESCRIPTION

- Fully coated, extra coating over entire hand
- Scalloped edge
- Rough finish over entire surface
- Antibacterial and anti-odour treatment
- Special hydrocarbon treatment
- Anatomical shape
- Seamless knit



BENEFITS

- A light, elastic low-lint glove, resistant to deformation and which keeps its shape longer
- Protects the hand from oils, hydrocarbons, grease and abrasion, with effective long lasting grip
- Impermeable for working in damp or greasy environments, enabling you to grip objects securely
- Surface provides tactile feel and better grip
- Greater hygiene
- Designed for easy movement and continuous wear
- No irritation by seams in contact with the skin
- Extended protection on the forearm

RECOMMENDED FOR THESE RISKS:

Cold
Chemicals
Abrasion
Tears

RECOMMENDED FOR THESE LINES OF WORK:

Chemical industry / Alkaline components
Chemical industry / Solvents
Construction / Painting

AVAILABLE SIZES

7/S • 8/M • 9/L • 10/XL • 11/XXL

LENGTH

Dependent on size, in mm (flat)

300-320

PACKAGING

Pairs per pack/box

10/120

COLOUR OF SUPPORT/COATING

Blue

THICKNESS

in mm

1,10

RECOMMENDATIONS FOR USE

- The size given corresponds to a well fitting glove
- The stated impermeability performance level (EN374-3) does not reflect the actual protection level at the place of work – other factors may influence the performance.
- Do not use with chemicals other than those tested without prior trials
- Highly traction resistant gloves, do not use if there is risk of being caught up in moving machines
- Store away from light and humidity
- Rinse the gloves in running water before removing, using a neutral detergent if necessary



Globus Building
38 Wheel Forge Way
Trafford Park, Manchester
M17 1EH

Tel: 0161 877 4747 Fax: 0161 877 4746
www.globus.co.uk

EC compliance certificate delivered by the notified body 0120 SGS United Kingdom Ltd., Systems & Services certification
202B Worle Parkway - Weston-super-Mare, BS22 6 WA - UK

The descriptions, characteristics, applications and photos are given for information purposes and do not constitute a contractual commitment. The manufacturer reserves the right to make any modifications it deems necessary.



ABRASION 0 1 2 3 4
CUTTING 0 1 2 3 4 5
TEARING 0 1 2 3 4
PUNCTURE 0 1 2 3 4



METHANOL 0 1 2 3 4 5 6
N-HEPTANE 0 1 2 3 4 5 6
HYDROCHLOR. ACID 36% 1 2 3 4 5 6

D - DICHLOROMETHAN 0 1 2 3 4 5 6
CAUSTIC SODA 40% 0 1 2 3 4 5 6
KEROSENE 1 2 3 4 5 6

F - TOLUENE 0 1 2 3 4 5 6
SULPHURIC ACID 96% 0 1 2 3 4 5 6

[Updated 01/02/2010]

