IRI-S

IRI-S, A SINGLE MODEL FOR THOUSANDS OF FACES

IRI-s, the first universal safety spectacles that fits perfectly to every / each face: a “memory form” B-Flex bridge, fully adjustable in height, depth and width, an ultra-enveloping frame with pivoting ergonomic temples, embraces precisely all face shapes, with or without reading area (clear version only)

PLATINUM

IRIPSI

IRIPSF

IRITWI

VERSIONS WITH READING AREA :
+1.5 : IRIDPSI1,5
+2 : IRIDPSI2
+2.5 : IRIDPSI2,5
+3 : IRIDPSI3

27 g

SUPPLIED WITH

Adjustable cord
Ref. CORDC

Optical insert

IRISRXKIT

Bi-color & bi-material temples

3 positions FLEX nose

- **1 MODEL - 1 SIZE**
- **PIVOTING, NON SLIP & ERGONOMIC TEMPLES**
- **CLEAR VERSION WITH READING AREA**
- **PLATINUM COATING (P)**
- **FLEX NOSE**

bollé SAFETY

IRI-S

IRI-S, A SINGLE MODEL FOR THOUSANDS OF FACES

MODEL	VERSIONS	REFERENCES	LENS MARKING	FRAME MARKING	COATINGS
IRI-s	Clear	IRIPSI	2C-1,2 1 FT KN CE	EN166 FT CE	Anti-scratch/Anti-fog
	Smoke	IRIPSF	5-3,1 1 FT KN CE	EN166 FT CE	Anti-scratch/Anti-fog
	Twilight	IRITWI	5-2 1 FT KN CE	EN166 FT CE	Anti-scratch/Anti-fog
	Reading area +1.5	IRIDPSI1.5	2C-1,2 1 FT CE	EN166 FT CE	Anti-scratch/Anti-fog
	Reading area +2	IRIDPSI2	2C-1,2 1 FT CE	EN166 FT CE	Anti-scratch/Anti-fog
	Reading area +2.5	IRIDPSI2.5	2C-1,2 1 FT CE	EN166 FT CE	Anti-scratch/Anti-fog
	Reading area +3	IRIDPSI3	2C-1,2 1 FT CE	EN166 FT CE	Anti-scratch/Anti-fog

LENS MARKING

Optical class symbols:

1. Continuous work

Mechanical strength symbols:

F. Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s
Maximum protection for glasses.

T. The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures.

Others symbols:

K. Resistance to surface damage by fine particles

N. Resistance to fogging

CE European standard Manufacturer name

TECHNOLOGY

TWILIGHT

The new B-twilight technology offers the advantages of PLATINUM with a double anti-fog coating (on both sides of the lenses) to prevent fogging in the most challenging conditions. Designed and used in low light conditions, it improves contrast. Its light transmission rate is perfect for outdoors, particularly early morning and late evening.
B-Twilight filters 76% of blue light.

FRAME MARKING

EN 166: Guaranteed minimum resistance of the protective eyewear against everyday risks including dropping the protective eyewear onto the ground, ageing by light exposure, exposure to heat or corrosion etc.

F. Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s
Maximum protection for glasses.

T. The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures.

CE European standard Manufacturer name

Bollé Safety product approval certificates to CE standards will be sent on request.

CLEANING AND STORAGE

CLEANING: The lenses should be cleaned regularly. Bollé Safety recommends only using the B-clean lens cleaning system.

MAINTENANCE: Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfiber pouch or rigid case.

STORAGE: All products must be stored in a dry and clean environment.

PACKAGING AND EAN13 CODE

	IRIPSI	IRIPSF	IRITWI	IRIDPSI1.5	IRIDPSI2	IRIDPSI2.5	IRIDPSI3
Individual plastic bag	3660740000264	3660740000271	3660740000288	3660740007003	3660740007010	3660740007027	3660740007034
10 safety spectacles / inner box	3660740100261	3660740100278	3660740100285	3660740107000	3660740107017	3660740107024	3660740107031
240 safety spectacles per outer pack	3660740200268	3660740200275	3660740200282	3660740207007	3660740207014	3660740207021	3660740207038

CHARACTERISTICS

LENSES	PC - 2,2 mm - Curve 10
FRAME	PC
TEMPLES	PC + TPR
STRAP	Non applicable
FOAM	Non applicable
SPARE LENSES	No

29/07/2014

Europe Bollé Safety
95 rue Louis Guérin
69100 Villeurbanne - France
Tél. : 00 33 (0) 4 78 85 23 64
Fax : 00 33 (0) 4 78 85 28 56
contact@bolle-safety.com

U.K. Bollé Safety
Unit C83 - Barwell Business Park Leatherhead Road - Chessington
Surrey - KT9 2NY
Tél. : 00 44 (0)208 391 4700
Fax : 00 44 (0)208 391 4733
e-mail : sales@bolle-safety.co.uk

bolle-safety.com