



350R

NITRILE COATED PALM GRIP GLOVE

A flexible and robust grip glove featuring a special synthetic nitrile rubber palm that protects against abrasion and oils.

FEATURES

- › A flexible, robust glove offering exceptional grip, dexterity and durability
- › Nitrile palm protects the hand from oils, hydrocarbons, grease and abrasion, with effective long lasting grip
- › Breathable back of hand to reduce perspiration
- › Rough surface to the nitrile provides a tactile feel and enhanced grip
- › Designed for easy movement and continuous wear
- › No irritation by seams in contact with the skin
- › No latex allergy risks
- › Elasticated wrist
- › 10 gauge seamless knit liner



SUITABLE FOR

Typical Industries

- Agriculture
- Construction
- Logistics
- Manufacturing
- Metallurgy
- Municipal Services
- Transport

Suitable Applications

- Handling Oily Components
- Heavy Duty Handling
- Maintenance
- Parks and Gardens
- Refuse Collection
- Warehousing

CERTIFICATION

CAT II



EN 388:2016



4132X

See overleaf for explanation





350R

PRODUCT INFORMATION

MATERIALS	LINER:	10 gauge polyester, cotton
	COATING:	Nitrile
COLOUR	Grey/green	
LENGTH (mm)	250 (size dependent)	
CUFF STYLE	Elasticated knit wrist	

RECOMMENDATIONS FOR USE

- **USE:** General handling glove. Not suitable for thermal, electrical or chemical protection. Do not use near moving machines if there is a risk of entanglement
- **STORAGE:** Store in dry conditions in the original packaging and away from direct sunlight
- **CLEANING:** To clean, wipe with a damp cloth. Note: The performance characteristics of worn and laundered gloves may differ from the results shown. Inspect the gloves to ensure no damage is present
- **LIFETIME:** Service life depends on the glove application and therefore cannot be specified. It is the responsibility of user to ensure the glove is suitable for its intended use

ORDERING DETAILS

SIZE	CODE	PACKAGING
7/S	SHO3501	10 pairs per bag
8/M	SHO3502	120 pairs per case
9/L	SHO3503	
10/XL	SHO3504	

CERTIFICATION LEGENDS



MECHANICAL HAZARDS EN 388:2016
PERFORMANCE LEVELS*

0-4	0-5	0-4	0-4	A-F	P
Abrasion Resistance		Circular Blade Cut Resistance	Tear Resistance	Puncture Resistance	Straight Blade Cut Resistance (EN ISO: 13997)
				Impact Resistance	

*If tests are not performed or are not applicable, 'X' will be placed instead of a number/letter

EUROPE

www.globusgroup.com

E: sales@globus.co.uk
T: +44 (0)161 877 4747
F: +44 (0)161 877 4746

MIDDLE EAST AND AFRICA

www.globusgroup.com/gcc

E: gcc@globusgroup.com
T: +971 4 882 9962
F: +971 4 882 9963



Globus Group, T2 Trafford Point, Twining Road, Trafford Park, Manchester, M17 1SH, UNITED KINGDOM
 Globus EMEA FZE, Jafza One, Tower A, Office 2201, Jebel Ali, PO Box 61195, Dubai, UNITED ARAB EMIRATES

©2020 Globus (Shetland) Ltd | SHO-DATA-350R-0620_1