

**Product Datasheet model super OTG 9169 260****UVEX ARBEITSSCHUTZ GMBH, Würzburger Str. 181-189,  
D-90766 Fürth**

<b>Product characteristics</b>	<ul style="list-style-type: none"><li>* Lightweight cover spectacle with unrestricted lateral vision</li><li>* Protective covering thanks to flat base curve</li><li>* Lens inclination of 11° ensures good view downwards and provides the wearer safeness from stumble-accidents</li><li>* x-stream-technology (XST) – flexible temple concept that adjusts to different wearing situations, with or without prescription glasses</li></ul>
<b>Technical details</b>	
<b>Frame</b>	<b>Front piece/Temple</b>
Material	PA/TPU
Features	XST-temple
Colour	navy blue-white

Manufacturer's ID code	<b>Marking</b> W
Applicable EN norm	166
Low-energy impact	F (45 m/s)
Conformity symbol	CE
<b>Lens</b>	
Material	PC
Thickness	2,1 mm
Coating	supravision excellence
Colour	clear
Filter	<b>Marking</b> 2C-1,2 (DIN EN 170)
Manufacturer's ID code	W
Optical class	1
Low-energy impact	F (45 m/s)
Surface resistance to fine particles	K
Antifog	N
<b>Miscellaneous</b>	
Weight	37 g
Packing	5 spectacles per box 160 spectacles per cardboard box
Standards	DIN EN 166 + DIN EN 170